



## LONG SPAN OPEN-WEB APPLICATION ADDITIONAL TERMS AND CONDITIONS

RedBuilt™ open-web trusses are to be erected and installed in an expert and safety-conscious manner and in accordance with the plans, the approved RedBuilt™ drawings and RedBuilt™ installation suggestions. Temporary construction loads, which cause member stresses beyond design limits, are not permitted.

Open-web truss clear spans beyond 70 feet and other spans detailed as requiring modular erection on RedBuilt™ drawings shall be erected in rigid modules at least 8 feet in width, accurately assembled in a jig with all bracing and final sheathing permanently and totally attached while on the ground. Specified bridging shall be installed in each module as detailed.

There must be an engineer and/or architect of record throughout the design and construction period of the project

Only structural panel sheathing will be permitted.

The contractor will give notification prior to enclosing the open-web truss system to permit RedBuilt™ personnel, should they desire, to review the installation.

Should purchaser fail to follow erection procedures as specified herein, purchaser agrees to hold harmless and indemnify RedBuilt™ for any and all losses sustained by RedBuilt™, including reasonable attorneys' fees, as a consequence of such failures.

**RedBuilt™**

**Purchaser**

Company: \_\_\_\_\_

By: \_\_\_\_\_

By: \_\_\_\_\_

Date: \_\_\_\_\_

Date: \_\_\_\_\_